

Actual

**Catalog Number:** 035-72775-7 **Product ID:** 7TBD012980R0010 **UPC Number:** 78621031926

Status: Active

3/4 Inch Insulated Watertight Strain Relief Connector, Straight, Cable Size 0.125 to 0.250 Inch, Steel, Zinc Plated

North American Specifications (UNSPSC)	
UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	T&B
Туре	Strain Relief Cord Connectors-Straight
Application	Provide Means for Passing a Cord Cable, Armored
	or Unarmored, Into an Enclosure, Through a Bulk-
	head or Into a Rigid Conduit
Size	0.125 to 0.250 Inch
Connection	Straight
Material	Steel
Finish	Zinc Plated

European Specifications (ETIM)		
ETIM	EC001180 Screw connection for protective metallic	
	hose	
Nominal size in inch	3/4 inch	
Model	Straight	
Revolving thread	N	
Construction type	External thread	
Connection type screw connection to	Thread	
housing		
Thread type	NPT	
Thread connection size	None	
Material housing	Steel	
Surface protection	Zinc coated	
Packaging		
Inner Quantity	10	
Inner Dimensions (inches)	4x4x3	
Outor Quantity	100	

Packaging	
Inner Quantity	10
Inner Dimensions (inches)	4x4x3
Outer Quantity	100
Outer Dimensions (inches)	21.5x8.5x3.5
Weight Uom	1 lbs. per 100

## For further technical assistance, please contact us...

**T&B Technical Support** MS 3B-50 8155 T&B Blvd. Memphis, TN 38125

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com