



Actual

Catalog Number: CLG2PSW
Product ID: 7TAI029670R0057
UPC Number: 78621093001
Status: Active

Non-Insulated Parallel Splice Connector For Wire Range 2 For Circular Mil Range 52,600-83,700 Length .7 Diameter .521, Metallic

- Resistant to corrosion and preserve the electrical integrity of the wires in single or multiple strands.
- Feature an intelligent constructable part number for quick identification of the wire range.
- Application Tools: WT115A, TBM8750M1, TBM8750BSCR

North American Specifications (UNSPSC)

UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Sta-Kon
Type	Splice Connector
Special Features	Resistant to corrosion and preserve the electrical integrity of the wires in single or multiple strands. Feature an intelligent constructable part number for quick identification of the wire range.
Material	Copper
Finish	Tin Plated
Color	Metallic
Voltage Rating	600V

European Specifications (ETIM)

ETIM	EC001059 Crimp splices for copper conductor
Insulation	None

Packaging

Inner Quantity	250
Inner Dimensions (inches)	5x4.5x3
Outer Quantity	2500
Outer Dimensions (inches)	24x11x3.5
Weight Uom	2 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com