

## Technical Information

### Metric PG-to-NPT Thread Adapters


| Cat. No.        | NPT Thread (mating) (in.) | Thread (at housing) |
|-----------------|---------------------------|---------------------|
| <b>PG11-38</b>  | 3/8                       | PG11                |
| <b>PG16-50</b>  | 1/2                       | PG16                |
| <b>PG21-75</b>  | 3/4                       | PG21                |
| <b>PG29-100</b> | 1                         | PG29                |
| <b>PG29-125</b> | 1-1/4                     | PG29                |
| <b>PG36-125</b> | 1-1/4                     | PG36                |
| <b>PG36-150</b> | 1-1/2                     | PG36                |
| <b>PG42-200</b> | 2                         | PG42                |



Supplied standard with all hoods and bases  
Special sizes/hood combinations available

### Metric ISO-to-NPT Thread Adapters

| Cat. No.       | NPT Thread (mating) (in.) | Thread (at housing) |
|----------------|---------------------------|---------------------|
| <b>M20-50</b>  | 1/2                       | M20                 |
| <b>M25-75</b>  | 3/4                       | M20                 |
| <b>M32-100</b> | 1                         | M32                 |



### Metric Cord Grip Connectors

| Cat. No.         | Cable O.D. (in.) |       | Thread (at housing) |
|------------------|------------------|-------|---------------------|
|                  | Min.             | Max.  |                     |
| <b>CG11-38</b>   | 0.200            | 0.470 | PG11                |
| <b>CG11-38P*</b> | 0.325            | 0.340 | PG11                |
| <b>CG135-50</b>  | 0.285            | 0.545 | PG13.5              |
| <b>CG16-50</b>   | 0.285            | 0.625 | PG16                |
| <b>CG21-75</b>   | 0.395            | 0.790 | PG21                |
| <b>CG29-100</b>  | 0.780            | 0.060 | PG291               |



Standard European style — can be specified/supplied with hoods and bases

\* Plastic