

Catalog Number: NVEZ-M202V/P4
Product ID: 7TCA292000R8530
UPC Number: 78621007966
EAN Number: 07630031213389
Status: Active

EMC Connector, Metric Thread - Thread Size M20x1.5, Conduit Size NW 12, Clamping Range 7.0-10.5, Color Black

North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	PMA
Type	Connectors-Straight
Application	EMC Sensitive Applications in Railway
Size	NW12
Material	Polyamide 6 with Nickel Plated Brass Threads
Insulation Class	IP68
Color	Black
Connection	M20
Temperature Rating	-40 Degrees C to 105 Degrees C; Short Term 160 Degrees C

European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	16mm
Degree of protection (IP)	IP68
Model	Straight
Revolving thread	N
Construction type	Internal thread
Type of connection	Snap connection
Thread type	Metric
Thread connection size	M20 x 1.5
Thread material	Brass
Thread length	6.5mm
Total length	54mm
Material	Polyamide
Material sealing	TPE
Colour	Black
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UR	N
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit Lloyd's Register	N
Operating temperature	-40 - +105°C

Packaging

Inner Quantity	50
Inner Dimensions (inches)	11.81x3.5x7.87
Outer Quantity	300
Outer Dimensions (inches)	15.748x11.811x8.661
Weight Uom	1 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com