## MULTI-WATT FAN FORCED UNIT HEATER





**FRONT** 

**BACK** 





- · Horizontal or Vertical Discharge
- Heavy gauge welded steel cabinet with powder coated finish and control compartment with a hinged and latched access door
- · Block finned steel element
- Automatic resetting type limit control to de-energize the heater should an over-heat situation occur
- Totally enclosed, single phase, permanently lubricated, thermally protected motor, mounted with rubber insulators to minimize vibration and noise
- · Individually adjustable louvers
- Hydraulic action capillary thermostat with an adjustable temperature range of 40°F to 90°F
- Heavy duty bracket standard on all models, allows mounting to wall or ceiling - Minimum mounting height - 6 feet
- Field Installed options disconnect switch

UPC										
686334	MODEL	WATTS	BTU's	VOLTS	PHASE	AMPS	TEMP RISE	AIR THROW	CFM	WT.
707282	HF5605T	5000	17,065	240	1	20.8	57 °F	16'	275	32 lb.
		4165	14,215			17.4	48 °F			
		3332	11,365			13.9	38 °F			
		2500	8533			10.4	29 °F			
		3750	12,798	208	1	18.0	43 °F	16'	275	32 lb.
		3123	10,659			15.0	36 °F			
		2500	8553			12.0	29 °F			
		1874	6396			9.0	21 °F			
707299	H3H5605T	5000	17,065	240	3	12.1	57 °F	16'	275	32 lb.
707305	P3P5605T	5000	17,065	480	3	6.1	57 °F	16'	275	32 lb.
707367	DCS-MT303	Optional Field Installed Disconnect Switch, 30 Amp @ 600Volts								